

Hydrostatic Pressure Type Level Transmitter

Model : SPL



Ordering Information

■ Hydrostatic Pressure Type Level Transmitter

SPL 1 A 1 A 1 A 10

CABLE EXTENSION
()M Per 1m

CONDUIT CONNECTION

A = None. (Std.)
B = PF 3/4"
C = PT 3/4"
D = PF 1/2"
E = PT 1/2"
F = NPT1/2"
G = NPT3/4"
OP= etc.

WEIGHT & SINKER

1 = None. (Std.)
2 = 304SS Weight only
3 = 304SS Weight & Sinker

TYPE OF WIRING

A = 2 Wire (Std.)

MEASURING RANGE (Side Mount : Consult office)

1 = 0 ~ 5m
2 = 0 ~ 10m
3 = 0 ~ 15m
4 = 0 ~ 20m
5 = 0 ~ 25m
6 = 0 ~ 30m

MOUNTING SIZE & JUNCTION BOX

A = None.
B = JIS 10K 50A FF Flange (Std.)
C = JIS 10K 65A FF Flange
D = JIS 10K 80A 6t FF Flange
E = JIS 10K 100A 6t FF Flange
OP = etc.

OUTPUT SIGNAL

1. 4~20mA / 2-wire (Std.)

■ General cable length : Measuring range + 2m only

■ When placing an order, selected ordering number should be indicated on the purchase order sheet.



14, Dunchon-daero 457beon-gil, Jungwon-gu
Seongnam-si, Gyeonggi-do, Korea[Zip.13218]

+82-31-627-9000 +82-31-624-5345

<http://www.seojin.biz>

2019 Edition Rev.0 (printed by Daumi)

■ Specifications subject to change without notice